FROSTLINE[™] MR16

FROSTED MR16 LAMPS FOR GENERAL LIGHTING

The USHIO Frostline™ series of MR16 lamps feature a Halogen capsule surrounded by a frosted reflector and frosted front glass cover. Because there is no reflective coating on the reflector, the light profile spills in all directions. Normal dichroic MR16s typically cause color changes or disruptive patterns on colored fixture glass. The Frostline series was designed to fit into pendant glass fixtures and eliminate the back-spill of "dichroic color" often occurring when used in these type of fixtures.


Available in - 20W, 35W, and 50W


FEATURES & BENEFITS:

- · Integrated Frosted Cover Glass
- · Diffused Light
- Crisp Halogen Color
- Standard Bi-Pin GU5.3 Base
- 4000 Hours Average Life
- Dimmable
- · A-Line Type Light Profile

APPLICATIONS:

- · Glass Pendant Lighting
- · Decorative Lighting





GU5.3

Case Quantity: 50

| Watts (W) | Ordering Code | Lamp Description FROSTLINE™ MR16, 2-Pin | Voltage (V) Base, C-8 Filament | Dimension MOL (in) | Color Temp (K) | Luminous Flux (Im) | Average Rated Life (h) |
|--------------|------------------|-----------------------------------------------|--------------------------------------|--------------------------|----------------------|--------------------------|------------------------------|
| 20 | 1003253 | JR12V-20W/FR/FG | 12 | 1.78 | 2900 | 250 | 4000 |
| 35 | 1003254 | JR12V-35W/FR/FG | 12 | 1.78 | 2900 | 520 | 4000 |
| 50 | 1003255 | JR12V-50W/FR/FG | 12 | 1.78 | 2950 | 850 | 4000 |

All dimensions shown in inches unless otherwise noted.



Frostline™ lamps are manufactured under ISO 9001 guidelines ensuring quality and security for the purchaser.

LAMP SOCKET

The model C-33U socket is rated up to 24V-7A for use with all low voltage USHIO GU5.3 based MR16 lamps. The metal clips secure the lamp firmly into the socket. Use Ordering Code 1002142.



